

Paper 7, TDC Part-3
Chapter– 1, Fundamental Concept of Digital
Electronics
Boolean Algebra Lecture 2

By:

Mayank Mausam
Assistant Professor (Guest Faculty)
Department of Electronics
L.S. College, BRA Bihar University,
Muzaffarpur, Bihar

Fundamental Concepts of Digital Electronics

11. Theorem No. 1.11) $A + A.B = A$

Proof of this theorem should be done by student himself.

12. Theorem No. 1.12) $A.(A + B) = A$

Proof of this theorem should be done by student himself.

Fundamental Concepts of Digital Electronics

13. Theorem No. 1.13) $A + \overline{A}.B = (A + B)$

Proof, As per theorem number 10, we can extend

$$\text{LHS, } A + A.B = (A + \overline{A}) (A + B)$$

$$= 1. (A + B) \quad [\text{As per theorem no. 7,}$$

$$A + \overline{A} = 1]$$

$$= (A + B)$$

14. Theorem No. 1.14) $A (\overline{A} + B) = AB$

15. Theorem No. 1.15) $AB + \overline{A}\overline{B} = \underline{A}$

16. Theorem No. 1.16) $(A + B) . (A + B) = A$

Fundamental Concepts of Digital Electronics

17.) Theorem No. 1.17) $AB + \bar{A}C = (A+C)(\bar{A}+B)$

proof, We will start by taking R.H.S

$$\begin{aligned}(A+C)(\bar{A}+B) &= A\bar{A} + \bar{A}C + AB + BC \\&= 0 + \bar{A}C + AB + BC \quad [A\bar{A} = 0] \\&= \bar{A}C + AB + BC \\&= \bar{A}C + AB + (A+\bar{A})BC \quad [(A+\bar{A}) = 1] \\&= \bar{A}C + AB + ABC + \bar{A}BC \\&= AB(1+C) + \bar{A}C(1+B) \\&= AB \cdot 1 + \bar{A}C \cdot 1 \quad [\text{As per Theorem no. 1.3}] \\&= AB + \bar{A}C \\&= \text{R.H.S.} \quad \text{Hence proved}\end{aligned}$$

18.) Theorem No. 1.18) $(A+B)(\bar{A}+C) = AC + \bar{A}B$

19.) Theorem No. 1.19) $AB + \bar{A}C + BC = AB + \bar{A}C$

No. 1.20) $(A+B)(\bar{A}+C)(B+C) = (A+B)(\bar{A}+C)$



Fundamental Concepts of Digital Electronics

De Morgan's Theorems:-

De Morgan's proposed 2 theorems, that are an important part of Boolean Algebra

DeMorgan's first Theorem states that;

The complement of 2 or more ANDed variables is equivalent to the OR of the complements of the individual variables.

OR,

The complement of a product of variables is equal to the sum of the complements of the variables.

Fundamental Concepts of Digital Electronics

OR,
The complement of a product of variables is equal to the sum of the complements of the variables.

$$\overline{AB} = \overline{A} + \overline{B}$$

11or, $\overline{ABC \dots N} = \overline{A} + \overline{B} + \overline{C} + \dots + \overline{N}$

De Morgan's 2nd theorem states that;

The complement of 2 or more ORed variables is equivalent to the AND of the complements of the individual variables.

OR,

Fundamental Concepts of Digital Electronics

The complement of a sum of variables is equal to the product of the complements of the variables.

i.e.,

$$\overline{A+B} = \bar{A} \cdot \bar{B}$$

Similarly,

$$\overline{A+B+C+\dots+N} = \bar{A} \cdot \bar{B} \cdot \bar{C} \cdot \dots \cdot \bar{N}$$

We have applied De Morgan's theorem during realization of OR gate using NAND gate on realization of AND gate using NOR gate.

Fundamental Concepts of Digital Electronics

So De Morgan's Theorem is useful in many Boolean Algebra.

Truth Table to Prove De Morgan's Theorem
 $\overline{A+B} = \bar{A} \cdot \bar{B}$

A	B	$\bar{A}$	$\bar{B}$	$A+B$	$\overline{A+B}$	$\bar{A} \cdot \bar{B}$
0	0	1	1	0	1	1
0	1	1	0	1	0	0
1	0	0	1	1	0	0
1	1	0	0	1	0	0

So from truth table we can see that values in column $\overline{A+B}$ equal to values in column $\bar{A} \cdot \bar{B}$.
Hence $\overline{A+B} = \bar{A} \cdot \bar{B}$

Fundamental Concepts of Digital Electronics

A logic problem can be specified in terms of a set of statements. This set of statements can be represented in terms of an equation called the logic equation or in terms of truth table.

A digital circuit uses logic gates for the implementation can realise a logic equation.

Using the different theorem, logic equation can be minimise (simplify). The simplified logic equation need less number of gates and/or less number of inputs for the gates.

Fundamental Concepts of Digital Electronics

Example) Simplify and realise (design) a digital circuit for the logic equation.

$$Y = \bar{A} \cdot B + A \cdot \bar{B} + \bar{A} \cdot \bar{B}$$

Soln.

Simplifying $Y = \bar{A}B + A\bar{B} + \bar{A}\bar{B}$

$$= \bar{A}B + \bar{B}(A + \bar{A})$$

$$= \bar{A}B + \bar{B} \cdot 1$$

$$= \bar{A}B + \bar{B}$$


$$= \bar{A} + \bar{B}$$

[As per Theorem no. 13]

Fundamental Concepts of Digital Electronics

Design using basic gates


$$Y = \bar{A} + \bar{B}$$



Design using NAND gates only.

$$Y = \bar{A} + \bar{B}$$

$$Y = \bar{A} + \bar{B} = \overline{\overline{\bar{A} + \bar{B}}} = \overline{\overline{\bar{A}} \cdot \overline{\bar{B}}} \quad \text{[As per De Morgan's theorem]}$$
$$= \overline{A \cdot B}$$



Fundamental Concepts of Digital Electronics

Integrated Circuit (IC) Gates

All the logic function (Gates) discussed are commercially available in 'IC' form.

For Example, IC-7400 is a quadruple 2-I/P NAND gate available in 14-pin DIP. This means IC-7400 contains 4-2-I/P NAND gates.

Figure below shows Block Diagram of 7400 IC




Figure 1.1) Block Diagram of 7400 IC

Fundamental Concepts of Digital Electronics

List of other ICs that contains gates like NOT, OR, AND, XOR etc is provided in the next slide. Different ICs with different number of gates, types of gate or with different numbers of input are available. As per the requirement we use that type of ICs.

The companies that manufacture these are: -

Texas Instruments

Philips

Fairchild Semiconductor

Motorola

Fundamental Concepts of Digital Electronics

IC No.	Description
7400	Quad 2-input NAND gates
7402	Quad 2-input NOR gates
7404	Hex inverters
7408	Quad 2-input AND gates
7410	Triple 3-input NAND gates
7411	Triple 3-input AND gates
7420	Dual 4-input NAND gates
7421	Dual 4-input AND gates
7427	Triple 3-input NOR gates
7430	8-input NAND gate
7432	Quad 2-input OR gates
7486, 74386	Quad EX-OR gates
74133	13-input NAND gate
74135	Quad EX-OR/NOR gates
74260	Dual 5-input NOR gates

Fundamental Concepts of Digital Electronics

Thank You